

# ST. CROIX PELLET INSERT AND STOVE SPECIFICATIONS

ELEMENT-P



ECLIPSE-P



ASHBY-P



PRESCOTT EXL



PRESCOTT EXP



HASTINGS



	ELEMENT-P	ECLIPSE-P	ASHBY-P	PRESCOTT EXL	PRESCOTT EXP	HASTINGS
Width	20 3/8"	25"	45" (with std. surround)	24 3/4"	24 3/4"	25"
Height	30 5/8"	35 5/8"	32" (with surround)	31 3/4"	34"	32 1/2"
Depth	20"	21 5/8"	24"	26"	26"	23 1/2"
Vent Size	3" rear vent	4" rear vent	3" rear vent	3" rear vent	3" rear vent	3" rear vent
Minimum Fireplace Opening (W)	—	—	24"	—	—	—
Minimum Fireplace Opening (H)	—	—	20 3/4"	—	—	—
Minimum Fireplace Opening (D)	—	—	16"	—	—	—
Heating Capacity <sup>1</sup>	Up to 1,800 sq. ft.	Up to 2,100 sq. ft.	Up to 1,800 sq. ft.	Up to 1,800 sq. ft.	Up to 1,800 sq. ft.	Up to 1,800 sq. ft.
Hopper Capacity <sup>2</sup>	45 lbs.	85 lbs.	60 lbs.	75 lbs.	75 lbs.	40 lbs.
Burn Rate <sup>3</sup> (lbs./hr.)	On/Off-4.5	On/Off-6.3	On/Off-4.5	On/Off-4.5	On/Off-4.5	On/Off-4.5
Emission Rate (g./hr.)	.660	1.562	.981	.532	.532	1.215
BTUH <sup>3</sup>	Up to 40,000	Up to 54,500	Up to 40,000	Up to 40,000	Up to 40,000	Up to 40,000
Ash Drawer	Yes	Yes	Yes	Yes	Yes	Yes
Electronic Ignition	Yes	Yes	Yes	Yes	Yes	Yes
Digital Controls	Yes	Yes	Yes	Yes	Yes	Yes
Room Thermostat	Yes	Yes	Yes	Yes	Yes	Yes
Shipping Weight	255 lbs.	400 lbs.	267 lbs.	285 lbs.	299 lbs.	427 lbs.

<sup>1</sup>Heating capacity will vary with home construction and climate.

<sup>2</sup>Hopper capacities will vary depending on the weight and volume of the fuel.

<sup>3</sup>Burn rate and BTUH will vary with fuel.

Certified to: ASTM E2779-2010 to 2020 phase, less than 2 g/hr

ASTM E1509-04 / U.L. 1482/U.L.C. S627

Oregon Administrative Rules: 814-23-900 thru 814-23-909

Power requirements: 120 Volts AC (Ignition: 400-500 watts,

Steady State: 200-250 watts)

